

# **HIK**VISION

## **CCTV Systems**

From Multi-Line, three decades of building trust.  
Through competitive pricing and quality.





## DVR and NVR



**DS-9600NI-I8 Series**  
NVR

### Features

- H.26 5/H.264+/H.264/MPEG4 video formats
- Up to 60 IP cameras can be connected
- Recording at up to 12 MP resolution
- Up to 8 SATA interfaces and 1 eSata interface connectable for recording and backup



**DS-7716/32NI-E4(-E4/16P)**  
Embedded NVR

### Features

- Third-party network cameras supported
- Up to 5 Megapixels resolution recording
- HDMI and VGA output at up to 1920×1080P resolution
- 16/32-ch network cameras can be connected with 100M/200M incoming bandwidth
- 4 SATA interfaces
- Plug & Play with 16 independent PoE network interfaces
- Support network detection, including network delay, packet loss, etc.

## Dome Cameras



**DS-2CD2122FWD-I (W)(S)**  
2MP WDR Fixed Dome Network Camera

### Features

- Up to 2MP high resolution
- IP66 weather-proof protection
- IK08 vandal-proof protection
- 4mm/6mm fixed lens
- 120dB Wide dynamic range
- 3D Digital Noise Reduction
- 3-axis adjustment
- Full HD1080p video
- Dual video streams
- DC12V and PoE
- Support H.264+
- Up to 30m IR range
- -S: Audio/Alarm IO
- -W: Built-in WiFi



**DS-2CD4125FWD-IZ**  
2MP Smart IP Indoor Dome Camera

### Features

- 1/2.8" Progressive Scan CMOS
- 1080p @ 60fps frame rate
- High light environment
- Support 128G on-board storage
- 2.80-12mm Motorized VF lens
- DC12V/PoE (802.3af)
- Slow shutter
- 140dB WDR
- Audio/Alarm IO
- Full Smart feature set
- Smart Auto Focus



**DS-2CD2100F-I Series**  
IR Dome Network Camera

### Features

- 1.3 MP/3 MP High Res.
- 3D DNR, DWDR, and BLC
- IR LEDs: Up to 100 Feet
- Up to 128 GB Storage
- IP66 Protection
- IK10 Vandal Resistant
- PoE (802.3af)
- HD Real-Time Video



**DS-2CD4126FWD-IZ**  
2MP Low Light Smart Camera

### Features

- 1/2.8" Progressive Scan CMOS
- Motorized lens with Smart Focus
- Support 64G on-board storage
- Full HD 1080p video
- Ultra-low light
- Up to 30m IR range
- Slow shutter
- 120dB WDR
- Audio/Alarm IO
- DC12V/PoE
- Smart Auto Focus

## Bullet Type Cameras



**DS-2CD2622FWD-I(Z)(S)**  
2MP WDR Vari-focal Bullet Network Camera



### Features

- 1/2.8" Progressive Scan CMOS
- Up to 2 megapixel resolution
- 120dB WDR
- 3D DNR
- Motorized lens 2.8-12mm (-Z)
- Up to 30 meters IR range
- Built-in Micro SD/SDHC/SDXC card slot, up to 128 GB
- Audio/alarm I/O (-S)
- Mobile Monitoring via EZVIZ P2P or iVMS-4500
- 12V DC±10% & PoE(802.3af)
- Support H.264+
- IP66 weather-proof protection



**DS-2CD2022WD-I**  
2MP WDR Mini Bullet Network Camera



### Features

- Up to 2 megapixel resolution
- Full HD 1080p video
- Dual video streams
- 4mm/6mm fixed lens
- 120dB Wide Dynamic Range
- 3D Digital Noise Reduction
- Backlight Compensation
- DC12V and PoE
- Up to 30m IR range
- 3-axis adjustment
- IP66 weather-proof protection
- Metallic housing and bracket
- Mobile Monitoring via EZVIZ P2P or iVMS-4500



**DS-2CD4025FWD-(A)(P)**  
2MP Smart IP Box Camera



### Features

- 1/2.8" Progressive Scan CMOS
- 1080p @ 60fps frame rate
- High light environment
- Slow shutter
- 140dB WDR
- -A: Auto Back Focus
- -P: P-Iris
- Audio/Alarm IO
- Support 128G on-board storage
- 2.80mm - 12mm Motorized VF lens
- Full Smart feature set



**DS-2CD4A26FWD-IZ(H)(S)**  
2MP Low Light Smart Bullet LPR Camera



### Features

- 1/1.8" Progressive Scan CMOS
- Full HD 1080p video
- Ultra-low light
- Slow shutter
- 120dB WDR
- Up to 50m IR range
- Motorized lens with Smart Focus, 2.8-12mm
- -H: build-in heater
- -S: audio/alarm IO
- Support 128G on-board storage
- DC12V/PoE
- IP67
- Smart Auto Focus

## PTZ Cameras



**DS-2DE7230W-AE**  
2MP 30X Network IR PTZ Dome Camera



### Features

- 1/2.8" Progressive Scan CMOS
- 3D intelligent positioning function
- Up to 150m IR distance
- Hi-PoE / 24VAC power supply
- DWDR
- 1920 x 1080
- 30X Optical Zoom
- Support cloud P2P



**DS-2DF6223-AEL**  
2MP 23X Network PTZ Dome Camera



### Features

- 1/1.9" HD CMOS sensor
- 1920x1080 Full HD, 23X Optical Zoom
- Ultra-low illumination
- 120dB True WDR
- Smart Tracking
- Smart Detection
- EIS (Electronic Image Stabilization)
- High-PoE / 24VAC power supply
- Vandal proof (IK10)



**DS-2DE5220W-AE(3)**  
2MP 20X Network PTZ Dome Camera



### Features

- 1/2.8" Progressive Scan CMOS
- 1920 x 1080
- 20x Optical Zoom
- DWDR
- 3D intelligent positioning function
- Support cloud P2P
- 24VAC and PoE (802.3at, Class 4)



**DS-2DF8223I-AEL(W)/36I-AEL(W)(B)**  
2MP 23/36X Network IR PTZ Dome Camera



### Features

- 1/1.9" HD CMOS sensor
- 1920x1080 Full HD, 23/36X Optical Zoom
- Ultra-low illumination
- 120dB True WDR
- Smart Tracking
- Smart Detection
- EIS (Electronic Image Stabilization)
- 200m IR distance
- High-PoE / 24VAC power supply
- Vandal proof (IK10)