




Features

- Excellent torsion strength
- · Even coating and various colors
- Excellent weather resistance
- Easy processing and installation
- Excellent impact resistance
- Outstanding fireproofing characteristics (Class A2 & B1)
- · Easy to maintain

Layer Composition



Specifications

- · Colors: 36 standard colors, also available in custom colors with minimum quantity.
- Applications: wall curtain, parapet and fascia, columns and canopies, advertising plates, interior walls, decorative fins
- Standard dimension: 1220 mm x 2440 mm
- · Thickness: 2mm, 3mm, 4mm, 5mm, 6mm
- *Sluminum skin thicknesses*: 0.12 mm, 0.15 mm, 0.21 mm, 0.25 mm, 0.30 mm, 0.35 mm, 0.40 mm, 0.45 mm, 0.50 mm
- Special sizes: maximum width 2000mm, maximum length 6m
- Finishes: PVDF or PE coating, single or double side coating
- Special products available:
 - 1220 (W) x any length x 2mm/3mm/4mm/5mm/6mm
 - 1250 (W) x any length x 2mm/3mm/4mm/5mm/6mm
 - 1500 (W) x any length x 2mm/3mm/4mm/5mm/6mm
 - 1550 (W) x any length x 2mm/3mm/4mm/5mm/6mm
 - 1570 (W) x any length x 2mm/3mm/4mm/5mm/6mm





